

iESPRITE® LTL LightMaster Side

iESPRITE® LTL LightMaster is an accessory of externally mounted programmable followspot handles with a control panel and two individual faders that allow you to create quality follow spot from the iESPRITE® LTL fixture.



Available in sideways mounted option, the handles feature two programmable faders (for example for dimmer and iris) and a control panel with touch screen display and four custom programmable jog-wheels and ten assignable buttons for a fully-customizeable user experience.

The programmable buttons, jog-wheels and faders allow the operator to comfortably trigger and control dimmer, iris, focus, zoom, frost, colors or other features of the unit. Internal fixture's settings allow you to fully tailor pan/tilt movement behavior by adjusting tension smoothness and resistance.

While in use by a follow spot operator, the remote desk can still take control of all the internal features of the unit (like dimmer, colors etc.).

Quick mounting in side position is assured by using quarter turn lock screws. The control panel connects to the unit via USB connection.

Technical Specification

Main features

- Activation button
- Blackout button
- Pan & Tilt freeze buttons
- User setting of controllable attributes
- 4 control jog-wheels
- 2 faders mounted on the handles with direct control of the key features 0-100% (for example dimmer and iris), assignable to any fixture properties (focus, zoom, frost, etc)
- 10 preset buttons with a direct access of the pre-programmed features
- Saving and uploading of custom settings
- Compatible with: iESPRITE® LTL WB

Control and programming

- Display: QVGA Robe touch screen with battery backup
- Movement control: manual

Electrical specification and connections

- Power and data connector in: USB B
- Ethernet port in/out: RJ45

Approvals

- CE Compliant
- cETLus Compliant

Mechanical specification

- Height: 190.8 mm (7.5")
- Width: 680.6 mm (26.8")
- Depth: 295.9 mm (11.7")
- Weight:
 - LightMaster side 3.2 kg (7.2 lbs)
 - Tripod 6.5 kg (17.2 lbs)
 - Adaptor for tripod 3.6 kg (7.9 lbs)
- Fixation option: iESPRITE® LTL WB

Included items

- Tripod:
 - 10980350
 - Min. height 60 cm (23.6")
 - Max. height 110 cm (43.3")
 - Black colour
- Adaptor for tripod: 99018543
- Spigot: 12052044
- USB-C to USB-B cable: 13053786

Optional accessories

- Single Top Loader Case: 10120221

Legal

- iESPRITE® is a Registered Trademark of Robe lighting s. r. o.
- iESPRITE® LTL LightMaster is patented by Robe lighting s. r. o. and is protected by one or more pending or issued patents